

PL-P8 Outdoor

General Indoor Fixed LED



Características :

- Panel de 960 x 960 mm que se adapta a su diseño.
- Admite montaje en pared, apilado y colgado, adaptándose a diversos entornos.

La calibración punto a punto garantiza la riqueza de colores y la uniformidad del brillo.



Technical Specification

Model

| | |
|-------|---------------|
| Model | PL-P8 Outdoor |
|-------|---------------|

Parameters

| | |
|--------------------------|----------------------------|
| Pixel Pitch | 8 mm |
| Pixel Configuration | 1R1G1B |
| LED Type | SMD2121 |
| Brightness (Max) | 6500 nit |
| Color Temperature | 3500K-9000K (adjustable) |
| Viewing Angle | H160° / V140° |
| Pixel Density | 15,625 dots/m ² |
| Module Size | 480mm×320mm |
| Module Resolution | 84×56 dots |
| Cabinet Size | W960mm×H960mm×D85mm |
| Cabinet Resolution (W×H) | 128×256 dots |
| Cabinet Weight | 11.45 kg ± 0.5 |
| Cabinet Material | Aluminum |

| | |
|---------------------------------|--|
| Operating Temperature/ Humidity | -10°C~+40°C/10~80%RH |
| Storage Temperature/ Humidity | -20°C~+60°C/10~80%RH |
| IP Rating | Front IP20/Rear IP20 |
| Aspect Ratio | 1:1 |
| Gray Scale | 14 bit |
| Contrast Ratio | 6000:1 |
| Refresh Rate | 3840Hz |
| Input Voltage | AC 110~220V (+/-10%) |
| Input Power (max) | 520 W/m ² |
| Input Power (Avg) | 120 W/m ² |
| Installation | Wall Mounted/Floor Mounted/Hanging |
| Maintenance | Front/Rear Maintenance |
| Signal Transmission Distance | CAT5 Cable (L≤100m), multi-mode fiber (L≤300m), single mode fiber (L≤10km) |

TELF: **908810787**
 MAIL: ventas@sistemasled.com
 WEB: www.sistemasled.com

